

## Technical product information

# calgodip Osmo Duo S

Udder cleaner and teat disinfectant



### Product benefits

- all in one product
- rapid efficacy in high germ pressure
- with care formula to prevent dehydration of the teat skin
- dipping, spraying and foaming
- excellent cleaning and disinfecting effect

### General Description

calgodip Osmo Duo S is a sprayable 2-component dipping agent based on chlorine dioxide which will be released after mixing of calgodip Osmo Duo Spray and calgodip Osmo Duo Active.

calgodip Osmo Duo S makes the teat free of germs thus prevents carry over of germs and ensures udder health.

calgodip Osmo Duo S is an all-in-one product for pre cleaning of udders and teat dipping.

calgodip Osmo Duo S provides rapid kill of germs and defense of environmental and cow specific germs.

This reduces mastitis rate and the risk of new diseases.

calgodip Osmo Duo S contains skin care components and ensures smooth teats.

### Application

- Give calgodip Osmo Duo Active and calgodip Osmo Duo Spray in equal quantities into the lower part of the dip cup.
- Mix well until the colour is homogeneously blue.
- The product is without contamination up to 36 hours at its maximum disinfecting efficiency.

Detailed data on the efficacy of the product are available in a separate microbiological product information.

After every milking dip the teat immediately in the fresh prepared solution or spray on it. An emollient layer around the teat is formed by this process which is reactivated by the influence of humidity.

Pre cleaning of the udder:

Spray on the teats with calgonit spray beaker or foam with calgonit foam dip beaker before milking. After a short reaction time wipe off with calgonit Euterpapier or calgonit Eutertuch DT.

### Technical Data

Appearance	cloudy, bluish liquid
Odour	slightly like chlorine
pH-value (conc.)	4,5
Storage	5°C - 35°C

**Ingredients** sodium chlorite, care components

For health and safety information, refer to the Safety Data Sheet (SDS) for this product.

### Hygienemanagement and Consulting

Calvatis GmbH

Am Hafen 16

68526 Ladenburg

Tel. +49 6203 105-0, Fax +49 6203 105-111

The function of this data sheet is to provide information on the application of the above product. The technical details included in this sheet with regard to the application of the product are based on current technical experience and are suitable for use in normal working conditions. In case of special or unusual working conditions, please consult our customer support service. Neither the data contained in this publication, nor recommendations made by either us or our application technology advisory service represent a legally binding guarantee of either the suitability of this product for a specific application nor of certain characteristics. We draw your attention in this respect to paragraph no. 5 of our General conditions of sale.