

Technical product information

tru-lit C-5

power cleaner



Product benefits

- excellent grease solving action
- removes tenacious soil
- economic in use

General Description

tru-lit C-5 is a powerful liquid detergent concentrate with a pleasant smell for application in commercial kitchens and other areas. Due to its special combination the product is especially suitable for removal of fatty and albuminous soil.

tru-lit C-5 is a very efficient cleaner for all washable surfaces like floors, tiles, tables and other devices.

Application

Spray tru-lit C-5 diluted with warm water (30-35°C) at the recommended concentration at the surface and use a scrub or sponge.

After cleaning rinse thoroughly with tap water.

Concentration:

3 to 6% for basic cleaning

1 to 2% for normal cleaning

5 to 10ml/l for maintenance cleaning

Dose by hand or dosing system.

Material Compatibility

tru-lit C-5 is not suitable for aluminium, zinc and copper.

Technical Data

Appearance	clear, yellow liquid
Odour	lemon scented
Density (g/cm ³)	1,057
p-value (5%)	3,35
Storage	2°C - 45°C

Handling references

tru-lit C-5 should be stored in closed containers between +5°C und +25°C.

Product is for professional use only.

Ingredients alkali, phosphates, surfactants, glycoles, dyestuff, fragrance

For health and safety information, refer to the Safety Data Sheet (SDS) for this product.

Hygienemanagement and Consulting

Calvatis GmbH
Dr. Albert-Reimann-Str. 16a
D-68526 Ladenburg
Tel. +49 6203 105-0
Fax +49 6203 105-111

Calvatis GmbH
Kaiser-Josef-Platz 41
A-4600 Wels
Tel. +43 7242 42899-0
Fax +43 7242 42899-22

Calvatis srl
C.-Abarth-Str. 17
I-39012 Meran
Tel. +39 0473 232016
Fax +39 0473 256820

Calvatis B.V.
Cop Balkplein
NL-3945 ER Cothen
Tel. +31 343 563959
Fax +31 343 561102

Calvatis AG
Mülistr. 3
CH-8852 Altendorf
Tel. +41 55 451 1010
Fax +41 55 451 1011

The function of this data sheet is to provide information on the application of the above product. The technical details included in this sheet with regard to the application of the product are based on current technical experience and are suitable for use in normal working conditions. In case of special or unusual working conditions, please consult our customer support service. Neither the data contained in this publication, nor recommendations made by either us or our application technology advisory service represent a legally binding guarantee of either the suitability of this product for a specific application nor of certain characteristics. We draw your attention in this respect to paragraph no. 5 of our General conditions of sale.