

Technical product information

tru-lit C-6

Highly alkaline oven and grill cleaner



Product benefits

- high content of actives
- removes difficult soil
- economic in use

General Description

tru-lit C-6 is a highly concentrated, phosphate free liquid product designed for the application in commercial kitchens. Because of its ideal combination of alkali, surfactants and solvents, heavily carbonised soils are removed.

tru-lit C-6 is especially suitable for cleaning of grills, ovens, broilers, chip pans and heavily fat-soiled surfaces.

Application

tru-lit C-6 is usually applied neat, but can also be used diluted up to 1:5 with water. It is sprayed on the heavily soiled equipment and left to work for 5 to 30 minutes depending on the grade of soiling. Loose deposits can be removed with a sponge and clear water.

Material Compatibility

tru-lit C-6 is not suitable for aluminium, galvanised steel, copper and brass.

Technical Data

Appearance	clear, brownish liquid
Odour	nearly odourless
p-Value (1%)	2,65
Storage	0°C - 45°C

Handling references

tru-lit C-6 should be stored in closed containers between +5°C und +25°C.

Product is for professional use only.

Ingredients Alkalies, surfactants, glycoles

For health and safety information, refer to the Safety Data Sheet (SDS) for this product.

Hygienemanagement and Consulting

Calvatis GmbH
Dr. Albert-Reimann-Str. 16a
D-68526 Ladenburg
Tel. +49 6203 105-0
Fax +49 6203 105-111

Calvatis GmbH
Kaiser-Josef-Platz 41
A-4600 Wels
Tel. +43 7242 42899-0
Fax +43 7242 42899-22

Calvatis srl
C.-Abarth-Str. 17
I-39012 Meran
Tel. +39 0473 232016
Fax +39 0473 256820

Calvatis B.V.
Cop Balkplein
NL-3945 ER Cothen
Tel. +31 343 563959
Fax +31 343 561102

Calvatis AG
Mülistr. 3
CH-8852 Altendorf
Tel. +41 55 451 1010
Fax +41 55 451 1011

The function of this data sheet is to provide information on the application of the above product. The technical details included in this sheet with regard to the application of the product are based on current technical experience and are suitable for use in normal working conditions. In case of special or unusual working conditions, please consult our customer support service. Neither the data contained in this publication, nor recommendations made by either us or our application technology advisory service represent a legally binding guarantee of either the suitability of this product for a specific application nor of certain characteristics. We draw your attention in this respect to paragraph no. 5 of our General conditions of sale.